

PRODUCT INFORMATION 3M Stationery and Office Supplies Division



Scotch™ No. 811 Removable Magic™ Tape

DESCRIPTION:

A transparent, low-tack, pressure-sensitive tape which is removable from most surfaces.

CHARACTERISTICS:

Backing:	Acetate.
Adhesive:	Post-it® adhesive
Tensile Strength:	15 lbs./1 in. width.
Elongation at Break:	15%.
Adhesion to Neenah Bond Paper:	83 gr./in. (ASTM D3330 - 83 Method A).
Total Thickness:	2 mils.

FEATURE	ADVANTAGE	BENEFIT
Premium quality matte finish backing	Matte/write-on surface can be written on with pencil, pen and other writing devices	Saves time and makes the job easier when mark-overs, notations, or corrections are needed.
	Moisture resistance	Repaired papers won't buckle and be destroyed, makes job easier and saves time
	Invisibility on the job	It will not shadow when copies are made, easy readability through the tape, saves time and money
	Easy to dispense, convenient	Saves time
	Extremely long aging and non-yellowing	Eliminates reapplication and duplication efforts to replace damaged work, thus saves time and money
Low, easy unwind	Tape breakage is eliminated	Tape is not wasted, frustrations of having to restart the roll are eliminated
Synthetic./Post-it® adhesive	Cleanly removable from most surfaces	Can be easily removed from originals without destroying them.
	Won't yellow or stain	Won't ruin originals causing duplication of work. Saves time and money

IMPORTANT NOTICE TO PURCHASER: All statements, technical information and recommendations contained herein are based on tests we believe to be reliable, but the accuracy or completeness thereof is not guaranteed, and, except where prohibited by law, the following is made in lieu of all express or implied rights, warranties and conditions, statutory or otherwise: Seller's and manufacturer's only obligation shall be to repair or replace, at manufacturer's option, such quantity of the product proved to be defective. Neither seller nor manufacturer shall be liable in Contract or in Tort, for any injury, loss or damage, direct, indirect, incidental, special or consequential, (including, without limitation, lost profits, goodwill, or business opportunity) arising out of the use of or the inability to use the product. Before using, user shall determine the suitability of the product for his intended use, and user assumes all risk and liability whatsoever in connection therewith.

No statement or recommendation not contained herein shall have any force or effect unless in an agreement signed by offices of seller and manufacturer.

Since the manufacturer of the product described in this document has no means of controlling the final use of the product by the consumer or user, it is the responsibility of the immediate purchaser and any intermediate seller(s) to inform the user of the purposes for which the product may be fit and suitable and of the properties of the product, including the precautionary measures which must be taken in order to ensure the safety of the users and of other third persons and property.

3

3M Canada Company
 Post Office Box 5757
 London, Ontario N6A 4T1

Laboratory studies have shown Scotch™ Removable Magic™ Tape #811 removes cleanly from most common office materials such as sulphite bond paper, 25% cotton bond paper, yellow legal paper, manila folders, #16 note paper, and most office surfaces such as painted wallboard, wallpaper, finished woods, metals, plastics and upholstery at normal office temperatures and humidity for a period of up to one year. If minor adhesive shedding should occur, the adhesive can be removed by:

1. Wiping with dry tissue type product.
2. Low abrasion / soft rubber eraser
3. Window cleaner
4. Rubbing alcohol

Test removability before using. Avoid use in applications where clean removability from clay coated or specially treated papers is required. May not remove cleanly from some blueprint papers. May tear or pick fibers from loose bond papers such as newsprint, Kraft paper, and paper products not manufactured by the screen process.

This product is not suitable for packaging applications. Avoid applications on lacquered finishes, blackboards, CIBA chrome, and other photographic paper, LEXAN plastic and leather.